

IMPORTANT NOTES: Read First


(A) Use liquid thread lock (such as Loctite®) with all threaded hardware. **Important:** Liquid thread lock (prior to curing) helps to eliminate the common problem of "thread seizure" in stainless steel hardware by serving as a lubricant during assembly.

(B) Do not pour concrete until the equipment is completely assembled, leveled and plumbed. Concrete must be allowed to cure completely before using the equipment (at least 72 hours).

(C) Refer to Installation Manual for 09 Collars and 11 Socket Clamps installation instructions.

(D) An appropriate energy absorbing safety surface is required under and around all playground equipment. Loose fill protective surfacing is shown only as an example for the purpose of this assembly instruction. Other surfacing material may vary in thickness and/or compression depths. See free publication - The Handbook for Public Playground Safety, Publication #325 at www.cpsc.gov for the surfacing appropriate for the fall height of the equipment or consult your surfacing supply representative.

FIGURE 1
NFuse Balance Step Bay



NOTE: NFuse Balance Step Bay shown. Other configurations will vary slightly, but does not affect assembly.

Step 1

Locate and attach collars at heights shown in Elevation View. (See Note B)

Refer to Footing Layout and mark footing hole locations. Dig 2 Ø12" footing holes. Refer to Footing Detail for depth and details.


IMPORTANT: For areas with soft soil conditions, larger footings may be required.

* Footing depth must be adjusted to compensate for the depth/thickness requirements of selected safety surfacing. See Section 06.1 of the Installation Manual.


** Height shown from finish grade to top of collar.

*** Height shown from top of collar to top of collar.

Elevation View



Top View - Footing Layout



Step 2 (Factory Assembled)

Attach Step Pad to Bottom Rail as shown in Figure 1.1. (See Note A)

NOTE: View below shows proper orientation of step pads as assembled.





Figure 1.1




Figure 1.2

Step 3

Attach Top Inside Rail and Anchor Plate to Frame as shown in Figure 1.2. (See Note A)

Step 4

Attach Top Outside Rail to Post as shown in Figure 1.3. (See Note A)




Figure 1.3

Step 5

For In-Ground Version Only

Attach NFuse Step Bay Bottom Rail to In-Ground Leg as shown in Figure 1.4. (See Note A)




Figure 1.4




Figure 1.5

Step 6

Attach NFuse Step Bay Bottom Rail to Frame as shown in Figure 1.5. (See Note A)




Figure 1.6

Step 7

Attach Socket Clamp Clevis to Collar as shown in Figure 1.6. (See Notes A & C)

Step 8

For Deck Mount Version Only

Attach Net Link Deck Connector to Deck as shown in Figure 2. (See Note A)




Figure 1.7




FIGURE 2

Step 9

Attach NFuse Balance Step Bay-Net to Socket Clamp Clevis as shown in Figure 1.7. (See Note A)

Step 10

For Non-Deck Mount Version Only

Attach Ladder Net to Socket Clamp Clevises using the same hardware shown in Figure 1.7. (See Note A)

Step 11

Attach remaining net connections to corresponding clevises as shown in Figure 1.8. (See Note A)

Step 12

Fully tighten all fasteners according to the "TIGHTENING TORQUE FOR HARDWARE" section of the Installation Manual.

Step 13

Plumb and level entire component. Pour concrete into footing holes. Allow at least 72 hours to cure before using this equipment. (See Note B)

Step 14

Place required protective surfacing under and around NFuse Balance Step Bay. (See Note D)




Figure 1.8

NFUSE BALANCE STEP BAY INSTALLATION INSTRUCTIONS

5202
Page 6 of 8

Parts List

IN-GROUND NON-DECK LINK		
Part #	DESCRIPTION	QTY
BE-1105	Socket Clamp Rope Clevis	12
FS-5201-BRK-L	NFuse Hex Net Bay - Bracket - Left	1
FS-5201-BRK-R	NFuse Hex Net Bay - Bracket - Right	1
FS-5201-TI	NFuse Hex Net Bay - Top Inside Weldment	1
FS-5202-T	NFuse Balance Step Bay - Top Outside Rail	1
GE-7015	Mounting Insert	12
GG-8125	Mounting Block 6 Top R3.5	2
GG-8127	Mounting Block 6 Bottom R3.5	2
HM-0001-IN	NFuse Hex Net Bay - Inner Net	1
HM-0001-TN	NFuse Hex Net Bay - Top Net	1
HM-0003	NFuse Balance Step Bay - Net	1
HS-1001-R35	Socket Clamp Set R3.5	2
HS-1001-R5	Socket Clamp Set R5	10
LM-0003	NFuse Balance Step Bay - Leg Tube	2
9103052-TR	Bolt Button Head 3/8" x 1"	34
9103200-TR	Bolt Button Head 3/8" x 1-7/16"	20
9103210-TR	Bolt Button Head 3/8" x 1-11/16"	12
9143112-TR	Bolt Shoulder 3/8" x 2-1/2" BH	2
9271062-TR	1/4" x 1-1/4" Tek Screw	4
9281062-5-TR	Screw Soc HD 1/4" x 1-3/8"	2
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	22
9333042	Washer Flat 3/8" x 7/8" O.D.	64
9345002	Washer Flat SAE 1/2"	4
9423002	Nut Lock Thin 3/8"	32
9443092-TR	Nut Barrel 3/8" x 2" BH	2

Assembled Parts List

ALL CONFIGURATIONS		
Part #	DESCRIPTION	QTY
EM-0001-NSP	NFuse Balance Step Bay - Net Step Pad	2
EM-0001-S	NFuse Balance Step Bay - Spacer	7
EM-0001-SP	NFuse Balance Step Bay - Step Pad	5
Varies	NFuse Balance Step Bay - Bottom Rail	1
9103092-TR	Bolt Button Head 3/8" x 2"	28
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	28
9333042	Washer Flat 3/8" x 7/8" O.D.	28
9413162-BLK	Nut Lock 3/8" w/ Black Cap	28

Parts List

SURFACE MOUNT NON-DECK LINK		
Part #	DESCRIPTION	QTY
BE-1105	Socket Clamp Rope Clevis	12
FS-5201-BRK-L	NFuse Hex Net Bay - Bracket - Left	1
FS-5201-BRK-R	NFuse Hex Net Bay - Bracket - Right	1
FS-5201-TI	NFuse Hex Net Bay - Top Inside Weldment	1
FS-5202-T	NFuse Balance Step Bay - Top Outside Rail	1
GE-7015	Mounting Insert	12
GG-8125	Mounting Block 6 Top R3.5	2
GG-8127	Mounting Block 6 Bottom R3.5	2
HM-0001-IN	NFuse Hex Net Bay - Inner Net	1
HM-0001-TN	NFuse Hex Net Bay - Top Net	1
HM-0003	NFuse Balance Step Bay - Net	1
HS-1001-R35	Socket Clamp Set R3.5	2
HS-1001-R5	Socket Clamp Set R5	10
9103052-TR	Bolt Button Head 3/8" x 1"	34
9103200-TR	Bolt Button Head 3/8" x 1-7/16"	20
9103210-TR	Bolt Button Head 3/8" x 1-11/16"	12
9143112-TR	Bolt Shoulder 3/8" x 2-1/2" BH	2
9281062-5-TR	Screw Soc HD 1/4" x 1-3/8"	2
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	22
9333042	Washer Flat 3/8" x 7/8" O.D.	64
9345002	Washer Flat SAE 1/2"	4
9423002	Nut Lock Thin 3/8"	32
9443092-TR	Nut Barrel 3/8" x 2" BH	2



www.playcraftsystems.com
For Customer Service Call
800.333.8519 (U.S.A.) or 541.955.9199 (International)

Rev B
9/27/2021

NFUSE BALANCE STEP BAY INSTALLATION INSTRUCTIONS

5202
Page 7 of 8

Parts List

IN-GROUND DECK LINK		
Part #	DESCRIPTION	QTY
BE-1105	Socket Clamp Rope Clevis	2
FS-1528	Angled Net Link Deck Connector	1
FS-5201-BRK-L	NFuse Hex Net Bay - Bracket - Left	1
FS-5201-BRK-R	NFuse Hex Net Bay - Bracket - Right	1
FS-5201-TI	NFuse Hex Net Bay - Top Inside Weldment	1
FS-5202-T	NFuse Balance Step Bay - Top Outside Rail	1
GE-7015	Mounting Insert	2
GG-8125	Mounting Block 6 Top R3.5	2
GG-8127	Mounting Block 6 Bottom R3.5	2
HM-0001-DN	NFuse Deck Link Net	2
HM-0001-TN	NFuse Hex Net Bay - Top Net	1
HM-0003	NFuse Balance Step Bay - Net	1
HS-1001-R35	Socket Clamp Set R3.5	2
LM-0003	NFuse Balance Step Bay - Leg Tube	2
9103052-TR	Bolt Button Head 3/8" x 1"	24
9103062-TR	Bolt Button Head 3/8" x 1-1/4"	4
9103200-TR	Bolt Button Head 3/8" x 1-7/16"	22
9103210-TR	Bolt Button Head 3/8" x 1-11/16"	2
9143112-TR	Bolt Shoulder 3/8" x 2-1/2" BH	2
9271062-TR	1/4" x 1-1/4" Tek Screw	4
9281062-5-TR	Screw Soc HD 1/4" x 1-3/8"	2
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	30
9333042	Washer Flat 3/8" x 7/8" O.D.	49
9345002	Washer Flat SAE 1/2"	4
9413002	Nut Lock 3/8"	4
9423002	Nut Lock Thin 3/8"	24
9443092-TR	Nut Barrel 3/8" x 2" BH	2

Assembled Parts List

ALL CONFIGURATIONS		
Part #	DESCRIPTION	QTY
EM-0001-NSP	NFuse Balance Step Bay - Net Step Pad	2
EM-0001-S	NFuse Balance Step Bay - Spacer	7
EM-0001-SP	NFuse Balance Step Bay - Step Pad	5
Varies	NFuse Balance Step Bay - Bottom Rail	1
9103092-TR	Bolt Button Head 3/8" x 2"	28
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	28
9333042	Washer Flat 3/8" x 7/8" O.D.	28
9413162-BLK	Nut Lock 3/8" w/ Black Cap	28

Parts List

SURFACE MOUNT DECK LINK		
Part #	DESCRIPTION	QTY
BE-1105	Socket Clamp Rope Clevis	2
FS-1528	Angled Net Link Deck Connector	1
FS-5201-BRK-L	NFuse Hex Net Bay - Bracket - Left	1
FS-5201-BRK-R	NFuse Hex Net Bay - Bracket - Right	1
FS-5201-TI	NFuse Hex Net Bay - Top Inside Weldment	1
FS-5202-T	NFuse Balance Step Bay - Top Outside Rail	1
GE-7015	Mounting Insert	2
GG-8125	Mounting Block 6 Top R3.5	2
GG-8127	Mounting Block 6 Bottom R3.5	2
HM-0001-DN	NFuse Deck Link Net	2
HM-0001-TN	NFuse Hex Net Bay - Top Net	1
HM-0003	NFuse Balance Step Bay - Net	1
HS-1001-R35	Socket Clamp Set R3.5	2
9103052-TR	Bolt Button Head 3/8" x 1"	24
9103062-TR	Bolt Button Head 3/8" x 1-1/4"	4
9103200-TR	Bolt Button Head 3/8" x 1-7/16"	22
9103210-TR	Bolt Button Head 3/8" x 1-11/16"	2
9143112-TR	Bolt Shoulder 3/8" x 2-1/2" BH	2
9281062-5-TR	Screw Soc HD 1/4" x 1-3/8"	2
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	30
9333042	Washer Flat 3/8" x 7/8" O.D.	49
9345002	Washer Flat SAE 1/2"	4
9413002	Nut Lock 3/8"	4
9423002	Nut Lock Thin 3/8"	24
9443092-TR	Nut Barrel 3/8" x 2" BH	2



www.playcraftsystems.com
For Customer Service Call
800.333.8519 (U.S.A.) or 541.955.9199 (International)

Rev B
9/27/2021

Specifications

SOCKET CLAMP ROPE CLEVIS:

Shall be precision cut and formed using 3/16" stainless steel.

NFUSE HEX NET BAY - BRACKET & ANGLED NET LINK DECK CONNECTOR:

Shall be fabricated using 1/4" sheet steel with welded 3/16" thick steel clevises and will have a multi-stage baked-on powder coat finish.

NFUSE BALANCE STEP BAY - INNER & OUTER RAIL:

Shall be fabricated using 2.375" O.D. 10 gauge steel tubing with welded 1/4" thick steel plates and 3/16" thick steel clevises and will have a multi-stage baked-on powder coat finish.

NFUSE BALANCE STEP BAY - BOTTOM RAIL

Shall be fabricated using 1.660" O.D. steel tubing with welded 1/4" thick steel plates and plugs and 3/16" thick stainless steel clevises. The NFuse Balance Step Bay - Bottom Rail shall have a multi-stage baked-on powder coat finish.

NFUSE BALANCE STEP BAY - NETS:

Shall be made from 16mm steel-reinforced rope with high-strength copolymer plastic intersection connectors and machined aluminum ferrules.

NFUSE BALANCE STEP BAY - STEP PADS:

Shall be made from high density 3/4" sheet plastic specially formulated for optimum UV stability and color retention.

NFUSE BALANCE STEP BAY - SPACER:

Shall be made from high density 1" sheet plastic specially formulated for optimum UV stability and color retention.

IN-GROUND LEG:

Shall be fabricated using 1.660" O.D. steel tubing. The In-Ground Leg shall have a multi-stage baked-on powder coat finish.

MOUNTING INSERTS:

Shall be precision die-cast from a high-strength aluminum alloy.

MOUNTING BLOCKS & SOCKET CLAMPS:

Shall be two-part and precision die-cast from a high strength aluminum alloy and will have a multi-stage baked-on powder coat finish.

HARDWARE:

Shall be stainless steel, zinc/nickel plated or galvanized as required to resist rust and corrosion.

Maintenance

Periodically tighten all screws, bolts and nuts. A periodic inspection of all parts is necessary. If a part is broken or worn, replace immediately. For general maintenance please refer to our Playground Maintenance Manual.

