


IMPORTANT NOTES: Read First

(A) Use liquid thread lock (such as Loctite[®]) with all threaded hardware. **Important:** Liquid thread lock (prior to curing) helps to eliminate the common problem of "thread seizure" in stainless steel hardware by serving as a lubricant during assembly.

(B) Refer to Installation Manual for 09 Collars and 11 Socket Clamps assembly instructions.

FIGURE 1
Curved Post Handle



NOTE: R3.5 Configuration shown. R5 will vary slightly, but does not affect the assembly.

Step 1

Locate collars at height shown in Side Elevation.
(See Note B).

Step 2

Attach Curved Post Handle to collars as shown in Figure 1.1. (See Notes A & B)

Step 3

Fully tighten all fasteners according to the "TIGHTENING TORQUE FOR HARDWARE" section of the Installation Manual.





Figure 1.1



SIDE ELEVATION

R3.5 Parts List

Part #	DESCRIPTION	QTY.
HS-1001-R35	Socket Clamp Set R3.5	2
FS-1313	Curved Post Handle	1

R5 Parts List

Part #	DESCRIPTION	QTY.
HS-1001-R5	Socket Clamp Set R5	2
FS-1313	Curved Post Handle	1

Specifications

CURVED POST HANDLE:

Shall be 1.315" O.D. 12 gauge steel tubing. Handle shall have a multi-stage baked-on powder coat finish.

Maintenance

Periodically tighten all screws, bolts and nuts. A periodic inspection of all parts is necessary. If a part is broken or worn, replace immediately. For general maintenance please refer to our Playground Maintenance Manual.