

IMPORTANT NOTES: Read First


(A) Use liquid thread lock (such as Loctite®) with all threaded hardware. **Important:** Liquid thread lock (prior to curing) helps to eliminate the common problem of "thread seizure" in stainless steel hardware by serving as a lubricant during assembly.

(B) Do not pour concrete until the equipment is completely assembled, leveled and plumbed. Concrete must be allowed to cure completely before using the equipment (at least 72 hours).

(C) **Important:** Chain Net Handholds assembly must be installed before completing the Chain Net Climber. Refer to 1221 Chain Net Climber assembly instructions during installation.

(D) Use appropriate compliant protective surfacing and adjust footing depths accordingly. See free publication - The Handbook for Public Playground Safety, Publication #325 at www.CPSC.gov for the surfacing appropriate for the fall height of the equipment or consult you surfacing supply representative.

FIGURE 1
Chain Net Handhold



NOTE: R5 4' deck height shown.
Other configurations will vary slightly,
but does not affect assembly.

Step 1

Refer to Footing Layout and mark footing hole locations. Dig (2) Ø 12" footing holes. Refer to Footing Detail for depth and details.

IMPORTANT: For areas with soft soil conditions, larger footings may be required. Additionally, half foot deck heights will require 6" deeper footing holes.


* Footing depth must be adjusted to compensate for the depth/thickness requirements of selected safety surfacing. See Section 06.1 of the Installation Manual.

Footing Distance Table


Center of Post to Center of Footing

Deck Height	x (in.)	x (mm)
30" to 48"	48-3/8	1229
54" to 72"	62-3/8	1585

Footing Detail



Top View - Footing Layout



Step 2

Place Chain Net Handholds into footing holes and attach to deck as shown in Figure 1.1. (See Notes A, B & C).

NOTE: Use (2) 3/8" x 1-3/4" Button Head Bolts included with Chain Net Handholds assembly.

Step 3

Fully tighten all fasteners according to the "TIGHTENING TORQUE FOR HARDWARE" section of the Installation Manual.

Step 4

Plumb and level entire component. Pour concrete into footing holes. Allow at least 72 hours to cure before using this equipment. (See Note B)

Step 5

Place appropriate compliant protective surfacing under and around Chain Net Handholds. (See Note D)




Figure 1.1

Specifications

CHAIN NET HANDHOLD:

Shall be fabricated using 1.315" O.D. steel tubing welded to 1/4" steel mounting plate. The Chain Net Handhold shall have a multi-stage baked-on powder coat finish.

HARDWARE:

Shall be stainless steel, zinc/nickel plated or galvanized as required to resist rust and corrosion.

Parts List

Part #	DESCRIPTION	QTY
Varies	Chain Net Handhold Set	1
9103082-TR	Bolt Button Head 3/8" x 1-3/4"	2
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	4
9413002	Nut Lock 3/8"	2

Maintenance

Periodically tighten all screws, bolts and nuts. A periodic inspection of all parts is necessary. If a part is broken or worn, replace immediately. For general maintenance please refer to our Playground Maintenance Manual.