


IMPORTANT NOTES: Read First

- (A) Use liquid thread lock (such as Loctite®) with all threaded hardware. **Important:** Liquid thread lock (prior to curing) helps to eliminate the common problem of "thread seizure" in stainless steel hardware by serving as a lubricant during assembly.
- (B) Do not pour concrete until the equipment is completely assembled, leveled and plumbed. Concrete must be allowed to cure completely before using the equipment (at least 72 hours).
- (C) All bolt threads protruding beyond the nut must be cut and de-burred until end is smooth to the touch. Sharp edges and/or points of any kind must be eliminated. A maximum of two threads may be exposed beyond the end of the nut.
- (D) Height of seat while unloaded and at rest, must be between 14" [360mm] and 28" [710mm] above the finish grade.
- (E) An appropriate energy absorbing safety surface is required under and around all playground equipment. Loose fill protective surfacing is shown only as an example for the purpose of this assembly instruction. Other surfacing material may vary in thickness and/or compression depths. See free publication - The Handbook for Public Playground Safety, Publication #325 at www.cpsc.gov for the surfacing appropriate for the fall height of the equipment or consult your surfacing supply representative.

FIGURE 1
Dual Airplane
Spring Rider




Step 1

Refer to Footing Layout and mark footing hole location. Dig (1) Ø 24" footing hole. Refer to Footing Detail for depth and details.


IMPORTANT: For areas with soft soil conditions, larger footings may be required.

* Footing depth must be adjusted to compensate for the depth/thickness requirements of selected safety surfacing. See Section 06.1 of the Installation Manual.

Footing Detail



Top View - Footing Layout
72" [1829mm] Use Zone Recommended



Step 2

Use the Single Spring Bottom Mount Plate as a template to create a plywood template for the placement of the anchor bolts. Attach anchor bolts to template as shown in Figure 2.

NOTE: Plywood not supplied.




FIGURE 3




FIGURE 2

Step 3

Pour concrete footing and level template on surface. Orient and set anchor bolts in concrete as shown in footing detail. Allow approximately 1" [25mm] of thread to protrude from the concrete as shown in Figure 3. Allow 72 hours to cure before proceeding to next step. (See Note B)

Step 4 (Factory Assembled)

Insert Event Spring Retainers into Spring and attach to Top Mount Plate and Bottom Mount Plate as shown in Figure 4. (See Note A)




FIGURE 4

Step 5 (Factory Assembled)

Attach Spring Rider Panels together as shown in Figure 5. (See Note A)




FIGURE 5

Step 6 (Factory Assembled)

Attach Spring Assembly and Mounting Spacer to Dual Airplane Body as shown in Figure 6. (See Note A)




FIGURE 6

Step 7

Attach Spring Rider Brackets to Dual Airplane Body as shown in Figure 7. (See Note A)




Figure 1.1




FIGURE 7

Step 8

Attach Handles, Seats and Footrests to Spring Rider Brackets where shown on Figure 1 using hardware as indicated by Figure 1.1. (See Note A)

Step 9

Attach Dual Airplane Spring Rider to Anchor Bolts as shown in Figure 1.2. (See Notes A & C)

Step 10

Fully tighten all fasteners according to the "TIGHTENING TORQUE FOR HARDWARE" section of the Installation Manual. (See Note B)

Step 11

Place appropriate compliant protective surfacing under and around Dual Airplane. (See Note E)




Figure 1.2

DUAL AIRPLANE INSTALLATION INSTRUCTIONS

PC-1395
Page 7 of 7

Parts List

Part #	DESCRIPTION	QTY
BE-4466	Spring Rider Bracket	12
EE-4938	Spring Rider Seat	2
EE-4939	Spring Rider Handle	2
EE-4940	Spring Rider Footrest	2
9103072-TR	Bolt Button Head 3/8" x 1-1/2"	12
9143112-TR	Bolt Shoulder 3/8" x 2-1/2" BH	6
9175393	Bolt Anchor 1/2" x 9-1/2" w/ Washer and Nut	6
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	24
9345002	Washer Flat SAE 1/2"	12
9413002	Nut Lock 3/8"	12
9443022-TR	Nut Barrel 3/8" x 5/8" BH	6

Assembled Parts List

Part #	DESCRIPTION	QTY
AE-4534	Double Spring Bottom Mount Plate	1
BE-4514	Event Spring Retainer	4
BE-4515	Single Spring Top Mount Plate	2
EE-4621-C	Dual Airplane Core	1
EE-4621-L	Dual Airplane - Left Side	1
EE-4621-R	Dual Airplane - Right Side	1
EE-4941	Spring Rider Mounting Spacer	4
HE-4498	Playground Event Spring	2
9103102-TR	Bolt Button Head 3/8" x 2-1/4"	9
9115092	Bolt Carriage 1/2" x 2"	8
9143112-TR	Bolt Shoulder 3/8" x 2-1/2" BH	6
9315003	Washer Cut 1/2" HDG	8
9333002	Washer Flat 3/8" x 1" O.D. x .100" thick	9
9345002	Washer Flat SAE 1/2"	21
9415132	Nut Lock 1/2"	8
9443022-TR	Nut Barrel 3/8" x 5/8" BH	9
9443092-TR	Nut Barrel 3/8" x 2" BH	6

Specifications

PANELS:

Dual Airplane Body, Seat, Handles, Footrests and Spacers shall be made from high-density 3/4" thick, hot extruded polyethylene sheet plastic specially formulated for optimum UV stability and color retention.

PLAYGROUND EVENT SPRING:

Shall be 5-3/4" O.D. with a free height of 14". The Playground Event Spring has a multi-stage baked-on powder coat finish.

EVENT SPRING RETAINER:

Shall be fabricated using 1/8" thick plate steel. The Event Spring Retainer has a multi-stage baked-on powder coat finish.

BOTTOM SPRING MOUNT PLATE:

Shall be fabricated using 1/4" thick plate steel. The Bottom Spring Mount Plate has a multi-stage baked-on powder coat finish.

TOP SPRING MOUNT PLATE:

Shall be fabricated using 3/16" thick plate steel. The Top Spring Mount Plate has a multi-stage baked-on powder coat finish.

SPRING RIDER BRACKET:

Shall be fabricated using 3/16" thick plate steel. The Spring Rider Bracket has a multi-stage baked-on powder coat finish.

HARDWARE:

Shall be stainless steel, zinc/nickel plated or galvanized as required to resist rust and corrosion.

Maintenance

Periodically tighten all screws, bolts and nuts. A periodic inspection of all parts is necessary. If a part is broken or worn, replace immediately. For general maintenance please refer to our Playground Maintenance Manual.



www.playcraftsystems.com
For Customer Service Call
800.333.8519 (U.S.A.) or 541.955.9199 (International)

Rev D
9/18/2019